

## **Product Specifications**

### **LED Helipad Light (White,Green,Yellow,Blue)**

- All aluminium construction
- All lights incapsulated
- IP65
- Size: Base plate 110mm x 110mm x 6mm Height: 19mm

#### **Electrical Details**

- 200 - 240 VAC
- 4 Watt
- 20 Milliamps
- Fully Dimmable
- Polarity Protected
- White 110 cd / yellow 80 cd / green 38 cd / blue 10 cd

### **LED Obstruction Light Pedestal (Red)**

- All aluminium construction
- All lights incapsulated
- IP65
- Size: Base plate 110mm x 110mm x 6mm Height: 19mm

#### **Electrical Details**

- 200 - 240 VAC
- 8 Watt
- 40 Milliamps
- Fully Dimmable
- Polarity Protected
- 35 cd

### **Identification Flashing Light Pedestal (White)**

- All aluminium construction
- All lights incapsulated
- IP65
- Size: Base plate 110mm x 110mm x 6mm

#### **Electrical Details**

- 200 - 240 VAC
- 4 Watt
- 20 Milliamps
- Flashing Rate:100 flashes per minute
- IP 65
- 2300 cd

### **LED Surface Floodlight (White)**

- All aluminium construction
- All lights incapsulated
- IP65
- Size: Base plate 110mm x 110mm x 6mm

#### **Electrical Details**

- 200-240 VAC
- 10 Watt
- 700 Milliamps

### **Concrete Anchors to host Lights**

- Strength 53 - 58 tons
- 150mm x 150mm x 150mm

### **LED Internal Lit Windsock with Red Obstruction Light**

- Alluminum, stainless steel, mild steel, galvanised or powder coated
- Nylon windsock ICAO approved material
- Sock size: 600mm dia x 2600mm
- Day glow orange

#### **Electrical Details**

- 8 Watt
- 40 Milliamps

### **Helipad Beacon Light**

- All aluminium construction
- IP65
- Size: Diameter 210mm Height: 310mm Weight: 12.9kg
- 32V DC at 12 Amps

#### **Light Output**

- White – 6800 lumens ( 160W Peak Power )
- Red – 2900 lumens ( 64W Peak Power )
- Green – 4700 lumens ( 97W Peak Power )
- Amber – 5700 lumens ( 120W Peak Power )

#### **Avg Power**

- White / Red : 115W
- White / Green : 130W
- White / Amber / Red : 114W
- White / Amber / Green : 125W